

J.CF - 3/8" metric crowfoot open end bits




Standards:

ASME B107.100

Description:

- Anti-slip design ensuring proper fitting on the fastener.
- Shaped to distribute the contact force over a larger surface.
- Suitable for use in confined spaces.
- Adapted to low torque uses.
- Sizes in mm: from 8 to 32
- Bright chrome finish.

	A [mm]	Length L1 [mm]	Thickness E [mm]	Weight [g]	Length L [mm]
J.10CF	10.0	23.6	8.0	25.0	34.2
J.11CF	11.0	23.6	8.0	32.0	34.8
J.12CF	12.0	27.9	8.0	35.0	37.4
J.13CF	13.0	27.9	8.0	37.0	37.9
J.14CF	14.0	30.0	8.0	40.0	38.5
J.15CF	15.0	34.3	8.0	45.0	41.1
J.16CF	16.0	34.3	8.0	49.0	42.2
J.17CF	17.0	35.8	8.0	54.0	43.6
J.18CF	18.0	40.9	8.0	59.0	48.9
J.19CF	19.0	40.9	8.0	61.0	49.5
J.21CF	21.0	43.9	8.0	65.0	53.4
J.22CF	22.0	43.9	8.0	68.0	56.3
J.23CF	23.0		8.0	75.0	59.4
J.24CF	24.0	51.3	8.0	80.0	60.7
J.27CF	27.0	51.3	8.0	90.0	59.8