

## J.CF - 3/8" metric crowfoot open end bits




### **Standards:**

**ASME B107.100**

### **Description:**

- Anti-slip design ensuring proper fitting on the fastener.
- Shaped to distribute the contact force over a larger surface.
- Suitable for use in confined spaces.
- Adapted to low torque uses.
- Sizes in mm: from 8 to 32
- Bright chrome finish.

	A [mm]	Length L1 [mm]	Thickness E [mm]	Weight [g]	Length L [mm]
<b>J.10CF</b>	10.0	23.6	8.0	25.0	34.2
<b>J.11CF</b>	11.0	23.6	8.0	32.0	34.8
<b>J.12CF</b>	12.0	27.9	8.0	35.0	37.4
<b>J.13CF</b>	13.0	27.9	8.0	37.0	37.9
<b>J.14CF</b>	14.0	30.0	8.0	40.0	38.5
<b>J.15CF</b>	15.0	34.3	8.0	45.0	41.1
<b>J.16CF</b>	16.0	34.3	8.0	49.0	42.2
<b>J.17CF</b>	17.0	35.8	8.0	54.0	43.6
<b>J.18CF</b>	18.0	40.9	8.0	59.0	48.9
<b>J.19CF</b>	19.0	40.9	8.0	61.0	49.5
<b>J.21CF</b>	21.0	43.9	8.0	65.0	53.4
<b>J.22CF</b>	22.0	43.9	8.0	68.0	56.3
<b>J.23CF</b>	23.0		8.0	75.0	59.4
<b>J.24CF</b>	24.0	51.3	8.0	80.0	60.7
<b>J.27CF</b>	27.0	51.3	8.0	90.0	59.8