


440 - Llaves mixtas métricas



Description:

-

	a [mm]	A [mm]	Longitud [mm]	Grosor [mm]	Grosor E1 [mm]	Grosor E2 [mm]	Cabeza Anchura si [mm]	Cabeza Anchura B1 [mm]	Peso [Kg]
440.10	10.0	10.0	145.0	4.2	7.6	5.2	23.0	15.0	0.04
440.10PB		10.0	145.0	4.2	7.6	5.2	23.0	15.0	0.04
440.11	11.0	11.0	155.0	4.6	8.1	5.5	24.5	16.9	0.05
440.11PB		11.0	155.0	4.6	8.1	5.5	24.5	16.9	0.05
440.12	12.0	12.0	162.0	4.4	8.4	5.8	27.0	18.0	0.06
440.12PB		12.0	162.0	4.4	8.4	5.8	27.0	18.0	0.06
440.13	13.0	13.0	170.0	4.8	8.6	6.1	28.7	19.3	0.07
440.13PB		13.0	170.0	4.8	8.6	6.1	28.7	19.3	0.07
440.14	14.0	14.0	180.0	5.7	9.5	6.4	31.0	21.1	0.085
440.14PB		14.0	180.0	5.7	9.5	6.4	31.0	21.1	0.085
440.15	15.0	15.0	185.0	5.9	10.0	6.8	32.6	22.2	0.095
440.15PB		15.0	185.0	5.9	10.0	6.8	32.6	22.2	0.095
440.16	16.0	16.0	195.0	6.4	10.5	7.3	35.6	23.9	0.115
440.16PB		16.0	195.0	6.4	10.5	7.3	35.6	23.9	0.115
440.17	17.0	17.0	202.0	6.5	10.9	7.6	37.0	25.3	0.13
440.17PB		17.0	202.0	6.5	10.9	7.6	37.0	25.3	0.13
440.18	18.0	18.0	208.0	7.2	11.4	8.1	38.7	26.0	0.15
440.18PB		18.0	208.0	7.2	11.4	8.1	38.7	26.0	0.15
440.19	19.0	19.0	216.0	7.2	11.9	8.3	41.2	27.8	0.17
440.19PB		19.0	216.0	7.2	11.9	8.3	41.2	27.8	0.17
440.20	20	20.0	224.0	6.3	12.3	8.6	43.1	29.5	0.185
440.21	21.0	21.0	233.0	7.8	12.8	8.8	45.4	30.9	0.205
440.21PB		21.0	233.0	7.8	12.8	8.8	45.4	30.9	0.205
440.22	22.0	22.0	248.0	8.3	13.3	9.0	46.9	32.3	0.23
440.22PB		22.0	248.0	8.3	13.3	9.0	46.9	32.3	0.23
440.23	23	23.0	257.0	8.7	13.8	9.3	49.0	33.6	0.255
440.23PB		23.0	257.0	8.7	13.8	9.3	49.0	33.6	0.255
440.24	24.0	24.0	267.0	8.9	14.2	9.7	51.0	35.0	0.29

440.24PB		24.0	267.0	8.9	14.2	9.7	51.0	35.0	0.29
440.25	25	25.0	274.0	9.4	14.7	9.9	53.0	36.4	0.315
440.25PB		25.0	274.0	9.4	14.7	9.9	53.0	36.4	0.315
440.26	26.0	26.0	285.0	9.8	15.1	10.1	55.5	37.8	0.345
440.26PB		26.0	285.0	9.8	15.1	10.1	55.5	37.8	0.345
440.27	27.0	27.0	295.0	8.9	15.6	10.4	58.0	39.2	0.375
440.27PB		27.0	295.0	8.9	15.6	10.4	58.0	39.2	0.375
440.28	28.0	28.0	305.0	10.6	16.1	10.7	60.7	40.6	0.415
440.28PB		28.0	305.0	10.6	16.1	10.7	60.7	40.6	0.415
440.29	29.0	29.0	320.0	10.8	16.6	11.2	63.0	42.0	0.475
440.29PB		29.0	320.0	10.8	16.6	11.2	63.0	42.0	0.475
440.30	30.0	30.0	340.0	11.2	17.1	11.5	65.0	43.5	0.53
440.30PB		30.0	340.0	11.2	17.1	11.5	65.0	43.5	0.53
440.32	32.0	32.0	355.0	11.5	18.0	12.5	68.0	46.1	0.64
440.33	33	33.0	380.0	11.8	18.5	12.8	69.8	47.0	0.715
440.34	34	34.0	390.0	12.8	19.0	13.0	72.0	48.9	0.745
440.35	35	35.0	430.0	12.8	19.5	13.5	74.3	51.0	0.89
440.36	36	36.0	440.0	13.2	20.0	14.0	76.0	53.0	0.945
440.38	38	38.0	450.0	14.1	22.0	15.2	80.0	56.0	1.1
440.41	41	41.0	460.0	14.7	23.0	16.0	85.0	58.3	1.3
440.4H	4	4.0	106.0	2.1	3.5	3.0	10.0	7.8	0.01
440.5.5H		5.5	115.0	3.1	6.0	3.8	13.3	9.2	0.015
440.5H	5	5.0	115.0	3.1	6.0	3.6	13.3	9.2	0.016
440.6	6	6.0	115.0	3.1	6.0	3.8	14.1	10.0	0.02
440.6PB		6.0	115.0	3.1	6.0	3.8	14.1	10.0	0.02
440.7	7.0	7.0	122.0	3.4	6.2	3.9	17.2	11.2	0.02
440.7PB		7.0	122.0	3.4	6.2	3.9	17.2	11.2	0.02
440.8	8.0	8.0	133.0	3.5	6.7	4.7	19.2	12.8	0.03
440.8PB		8.0	133.0	3.5	6.7	4.7	19.2	12.8	0.03
440.9	9	9.0	138.0	3.9	7.1	4.7	21.2	14.2	0.035
440.9PB		9.0	138.0	3.9	7.1	4.7	21.2	14.2	0.035