

76 - Forged metric 12 x 6 point angled open-socket wrenches




Standards:

NF ISO 2236, NF ISO 691, ISO 2236, ISO 691, DIN ISO 691

Description:

- Angled socket wrenches: wrenches designed for powerful unlocking.
- 12-point short head for 30° increment and 6-point long head.
- Opening of the short head for passing threaded rods.
- Metric sizes: 6 to 38 mm.
- Presentation: satin chrome finish.

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length [mm]	Length L1 [mm]	Head Width B [mm]	Height H [mm]
76.10	10	8.0	7.0	129.0	28.0	15.0	24.0
76.10PB	10	8.0	7.0	129.0	28.0	15.0	24.0
76.11	11	8.0	7.0	136.0	30.0	16.5	25.0
76.11PB	11	8.0	7.0	136.0	30.0	16.5	25.0
76.12	12	9.0	8.0	144.0	36.0	18.0	28.0
76.12PB	12	9.0	8.0	144.0	36.0	18.0	28.0
76.13	13	9.0	8.0	152.0	38.0	19.5	30.0
76.13PB	13	9.0	8.0	152.0	38.0	19.5	30.0
76.14	14	10.5	9.0	160.0	40.0	21.0	32.0
76.14PB	14	10.5	9.0	160.0	40.0	21.0	32.0
76.15	15	10.5	10.0	169.0	42.0	22.5	34.0
76.15PB	15	10.5	10.0	169.0	42.0	22.5	34.0
76.16	16	13.0	12.0	178.0	46.0	24.0	37.0
76.16PB	16	13.0	12.0	178.0	46.0	24.0	37.0
76.17	13	13.0	12.0	187.0	48.0	25.5	39.0
76.17PB	13	13.0	12.0	187.0	48.0	25.5	39.0
76.18	18	13.0	12.0	195.0	50.0	26.5	40.0
76.18PB	18	13.0	12.0	195.0	50.0	26.5	40.0
76.19	19	15.0	12.0	204.0	51.0	28.5	41.0
76.19PB	19	15.0	12.0	204.0	51.0	28.5	41.0
76.20	20	15.0	13.0	212.0	53.0	29.5	43.0
76.20PB	20	15.0	13.0	212.0	53.0	29.5	43.0
76.21	21	15.0	14.0	221.0	55.0	30.5	46.0
76.21PB	21	15.0	14.0	221.0	55.0	30.5	46.0
76.22	22	15.0	14.0	230.0	57.0	32.0	48.0
76.22PB	22	15.0	14.0	230.0	57.0	32.0	48.0
76.23	23	18.0	15.0	240.0	64.0	33.5	51.0

76.23PB	23	18.0	15.0	240.0	64.0	33.5	51.0
76.24	24	18.0	16.0	250.0	67.0	34.5	54.0
76.24PB	24	18.0	16.0	250.0	67.0	34.5	54.0
76.25	25	20.0	17.0	260.0	69.0	36.0	56.0
76.26	26	20.0	17.0	270.0	70.0	37.0	57.0
76.27	27	22.0	19.0	280.0	73.0	38.0	58.0
76.28	28	22.0	19.0	290.0	75.0	39.5	60.0
76.29	29	22.0	19.0	300.0	76.0	41.0	62.0
76.30	30	24.0	21.0	310.0	83.0	42.0	64.0
76.31	31	24.0	22.6	320.0	86.0	43.5	70.0
76.32	32	24.0	22.6	330.0	88.0	44.5	74.0
76.36	36	27.0	24.0	370.0	97.0	49.5	82.0
76.6	6	4.5	4.5	102.0	21.0	10.0	16.0
76.6PB	6	4.5	4.5	102.0	21.0	10.0	16.0
76.7	7	4.5	4.5	106.0	22.0	11.0	17.0
76.7PB	7	4.5	4.5	106.0	22.0	11.0	17.0
76.8	8	7.0	6.0	114.0	25.0	12.5	19.0
76.8PB	8	7.0	6.0	114.0	25.0	12.5	19.0
76.9	9	7.0	6.0	122.0	26.0	13.5	20.0
76.9PB	9	7.0	6.0	122.0	26.0	13.5	20.0