

249.GSLS - Sheathed drift punch - SLS



Description:

- Tool fitted with a FACOM SLS attachment solution, preventing any risk of accidental falls.
- The "turning" crimped cable solution, chosen and tested by FACOM, preserves the ergonomics of use of the tool.
- Long stem.
- Head hardness 43 HRc.
- Stem hardness 58 HRc.

| =• | A [mm] | Length L [mm] | Diameter [mm] | Weight [g] | Length L1 [mm] | Length L2 [mm] |
|-----------|--------|---------------------|------------------|---------------|----------------------|----------------------|
| 249.G2SLS | 1.95 | 140.0 | 8.0 | 65.0 | 35.0 | 105.0 |
| 249.G3SLS | 2.95 | 150.0 | 8.0 | 65.0 | 45.0 | 105.0 |
| 249.G4SLS | 3.95 | 190.0 | 10.0 | 110.0 | 60.0 | 105.0 |
| 249.G5SLS | 4.95 | 200.0 | 10.0 | 110.0 | 70.0 | 105.0 |
| 249.G6SLS | 5.9 | 210.0 | 12.0 | 155.0 | 80.0 | 105.0 |
| 249.G8SLS | 7.9 | 216.0 | 12.0 | 170.0 | 86.0 | 105.0 |