

75 - Forged metric 6 x 6 point angled open-socket wrenches




Standards:

NF ISO 2236, NF ISO 691, ISO 2236, ISO 691, DIN ISO 691

Description:

- Angled socket wrenches: wrenches designed for powerful unlocking.
- Short head and long head: 6-point.
- Opening of the short head for passing threaded rods.
- Metric sizes: 6 to 38 mm.
- Presentation: satin chrome finish.

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length [mm]	Length L1 [mm]	Head Width B [mm]	Height H [mm]
75.10	10	8.0	7.0	129.0	28.0	15.0	24.0
75.10PB	10	8.0	7.0	129.0	28.0	15.0	24.0
75.11	11	8.0	7.0	136.0	30.0	16.5	25.0
75.11PB	11	8.0	7.0	136.0	30.0	16.5	25.0
75.12	12	9.0	8.0	144.0	36.0	18.0	28.0
75.12PB	12	9.0	8.0	144.0	36.0	18.0	28.0
75.13	13	9.0	8.0	152.0	38.0	19.5	30.0
75.13PB	13	9.0	8.0	152.0	38.0	19.5	30.0
75.14	14	10.5	9.0	160.0	40.0	21.0	32.0
75.14PB	14	10.5	9.0	160.0	40.0	21.0	32.0
75.15	15	10.5	10.0	169.0	42.0	22.5	34.0
75.15PB	15	10.5	10.0	169.0	42.0	22.5	34.0
75.16	16	13.0	12.0	178.0	46.0	24.0	37.0
75.16PB	16	13.0	12.0	178.0	46.0	24.0	37.0
75.17	17	13.0	12.0	187.0	48.0	25.5	39.0
75.17PB	17	13.0	12.0	187.0	48.0	25.5	39.0
75.18	18	13	12.0	195	50	26.5	40.0
75.18PB	18	13.0	12.0	195.0	50.0	26.5	40.0
75.19	19	15.0	12.0	204.0	51.0	28.5	41.0
75.19PB	19	15.0	12.0	204.0	51.0	28.5	41.0
75.20	20	15.0	13.0	212.0	53.0	29.5	43.0
75.21	21	15.0	14.0	221.0	55.0	30.5	46.0
75.22	22	15.0	14.0	230.0	57.0	32.0	48.0
75.23	23	18.0	15.0	240.0	64.0	33.5	51.0
75.24	24	18.0	16.0	250.0	67.0	34.5	54.0
75.25	25	20.0	17.0	260.0	69.0	36.0	56.0
75.26	26	20.0	17.0	270.0	70.0	37.0	57.0

75.27	27	22.0	19.0	280.0	73.0	38.0	58.0
75.28	28	22.0	19.0	290.0	75.0	39.5	60.0
75.29	29	22.0	19.0	300.0	76.0	41.0	62.0
75.30	30	24.0	21.0	310.0	83.0	42.0	64.0
75.31	31	24.0	22.6	320.0	86.0	43.5	70.0
75.32	32	24.0	22.6	330.0	88.0	44.5	74.0
75.33	33	27.0	24.0	340.0	92.0	46.0	79.0
75.34	34	27.0	24.0	350.0	95.0	47.0	80.0
75.35	35	27.0	24.0	360.0	96.0	48.5	81.0
75.36	36	27.0	24.0	370.0	97.0	49.5	82.0
75.38	38	28.0	25.0	390.0	99.0	52.0	85.0
75.6	6	4.5	4.5	102.0	21.0	10.0	15.0
75.6PB	6	4.5	4.5	102.0	21.0	10.0	15.0
75.7	7	4.5	4.5	106.0	22.0	11.0	17.0
75.7PB	7	4.5	4.5	106.0	22.0	11.0	17.0
75.8	8	7.0	6.0	114.0	25.0	12.5	19.0
75.8PB	8	7.0	6.0	114.0	25.0	12.5	19.0
75.9	9	7.0	6.0	122.0	26.0	13.5	20.0
75.9PB	9	7.0	6.0	122.0	26.0	13.5	20.0